

## Survey on Approaches to Eliminate Harmful Microorganisms in Food Technology Based On Ultrasonic Waves

Amir Hossein Ghadimi<sup>1\*</sup> and Nazanin Kordestanian<sup>2</sup>

<sup>1</sup>Department of Food Science and technology, Yasooj Branch, Islamic Azad University, Iran.

<sup>2</sup>Department of biology, Shiraz University, Iran.

<http://dx.doi.org/10.13005/bbra/2442>

(Received: 05 March 2017; accepted: 08 March 2017)

There of various methods to remove microorganisms which can active harmful enzymes in food. Also researchers and scientists are going to find methods for food preservation based on reduction of the heat treatments needed. Utilized methods are divided to thermal methods and non-thermal methods as two main approaches. One of the most important non-thermal methods is ultrasonic. This method is sometimes combined with heat treatment. However it can be used as an alternative method to heat. Texture, concentration measurements, foods and vegetables composition determination, thickness, monitoring and controlling several processes by considering flow level and temperature measurements for food packages are other industrial applications of ultrasound.

**Keywords:** Non-thermal methods, Food technology, Ultrasonic waves, Microorganism.

---

In the food industry, eliminating harmful microorganisms and inactivating enzymes are important for food quality and also for public health. That is the reason why heat treatment is the most utilized method for stabilizing foods because of its capacity to destroy microorganisms and also to inactivate enzymes. However, since heat can alter the organoleptic properties of foods and diminish the contents or bioavailability of some nutrients, there is a growing interest in searching for methods that are able to reduce the intensity of the heat treatments needed for food preservation<sup>17</sup>.

In order to reduce the detrimental effects of heat treatment, heat is combined with other physical and chemical agents to increase the lethal action; in addition, non-thermal alternatives are

being tried. Some of the common non-thermal alternatives to conventional thermal processing of foods include; pulse-electric field inactivation, microfiltration, pulse-light inactivation, high pressure and ultrasonication<sup>8,17,20</sup>. Ultrasonication combined with heat can accelerate the rate of sterilization of foods, thus

lessening both duration and intensity of thermal treatment and the resulting damage. The advantages of ultrasound over heat treatment include: Minimization of flavor loss, especially in sweet juices; greater homogeneity and significant energy savings<sup>10</sup>. There are many other methods that can be combined with ultrasound other than heat.

### Ultrasonic treatment

Ultrasonic irradiation has the potential to be used for the inactivation of bacterial populations. Investigation of ultrasound as a potential microbial inactivation method began in

---

\* To whom all correspondence should be addressed.  
E-mail: [ahghadimi67@gmail.com](mailto:ahghadimi67@gmail.com)

the 1960s, after it was discovered that the sound waves used in anti-submarine warfare killed fish<sup>10</sup>.

According to another source; the inactivation of microorganisms by Ultrasonic Waves (UW) was reported in the early 1930s but its scant lethal effect prevented its use as a sterilization method. However, improvements in UW generation technology over the last few decades have stimulated the interest of investigators in microbial inactivation by UW<sup>25</sup>.

In<sup>30</sup> the lethal effects of ultrasound on spore forming bacteria has been studied. Combination of heat and high power UW (20 kHz) was first explored in<sup>23</sup> and the term of thermoultrasonication was used. According to this study in<sup>24</sup> the inactivation effect of thermoultrasonication was greater than UW at room temperature. More recently, the term Manothermosonication (MTS), which is the combination of heat, pressure and ultrasound has been coined for the combined treatments<sup>23</sup>.

A resistometer was designed and built to apply high-power UW under pressure at nonlethal (manosonication) and lethal (manothermosonication) temperatures. The results indicated that the rate of vegetative cell inactivation by Manosonication (MS) increased when the static pressure was raised. It was also observed that the inactivation rate by MS increased exponentially with the amplitude of UW<sup>22,26</sup>.

#### **Ultrasonication in food technology**

The use of ultrasonication is still being studied with because of the advent of many applications. Although the possibility of deactivating enzymes or destroying microorganisms by ultrasound waves, alone or in combination with other physical treatments, has been widely used in for laboratory, the same is not true for industry. One of the reasons for that is the lack of information needed for design and scale-up procedure<sup>19</sup>.

MTS (Manothermosonication) has been shown to inactivate several enzymes and microorganisms much more rapidly than heat treatment at identical temperatures. The industrial use of MTS could therefore reduce substantially treatment times of several foods. But before MTS can be industrially used, its effects on several quality parameters of these individual foods need to be studied<sup>34</sup>.

#### **Ultrasonic methods other than microbial inactivation**

The industrial applications of ultrasound include texture, viscosity and concentration measurements of many solid or fluid foods; composition determination of eggs, meats, fruits and vegetables, dairy and other products; thickness, flow level and temperature measurements for monitoring several processes; and non-destructive inspection of egg shells and food packages. Also, the direct process improvements such as cleaning surfaces, enhancement of dewatering, drying and filtration, disruption of cells, degassing of liquids, acceleration of heat transfer and extraction process and enhancement of any process dependent upon diffusion are ways that UW can be used in food technology.

Homogenization is an important and necessary pretreatment in milk processing. Ultrasound application in milk homogenization is noteworthy in recent studies. Improvements over conventional homogenization can lead to yogurt of superior quality<sup>38</sup>.

In order to evaluate the effect of ultrasound on the fermentation, three treatments were investigated. One of these was the control group in which the yogurts were manufactured by the conventional method. The other group was treated by ultrasound before the milk was inoculated with yogurt starter cultures. For the last treatment group, ultrasonication was applied after inoculation with starter but before the fermentation stage. Treatment with UW before inoculation resulted in an increase in water holding capacity and a decrease in syneresis. Treatment after inoculation resulted in a decreased fermentation time by 30 min and increased water holding capacity but arguably no beneficial effect on syneresis<sup>38</sup>.

In the experimental study<sup>36</sup> a reduction of 74 % in the size of the fat globule was observed after the treatment of milk by continuous-flow ultrasonic treatment at temperatures close to 60°C. They concluded that continuous-flow ultrasonic treatment of milk could be a promising milk preservation technique, especially when used in combination with sub-pasteurization temperatures such as thermisation. The microbiological quality of milk could be enhanced comparable to conventionally thermised milk and, at the same time,

the reduction in the size of the fat globules makes this technique practical. However, more research is needed<sup>36</sup>.

LIU (Low Intensity Ultrasound) can be applied to several stages of the cheese making process<sup>5</sup>. This technique was tried for determining the optimum cut time in the coagulation step. The quality control of some manufactured cheese includes the detection of internal cracks due to abnormal fermentations, classification according to the ripening time as well as the non-destructive assessment of the composition of cheese blocks. The optimum rennet cut time, cheese composition and textural properties can be non-destructively determined using LIU. The existence of internal cracks resulting from freezing can also be detected. These technologies should be considered for different types of cheese for a wide range of applications including mould and pocket distribution assessment. As long as these measurements are non-destructive, the equipment should be designed to consider the assessment of a company's entire production<sup>5</sup>.

A specially designed ultrasound device has been applied to cheese manufacturing. The results showed that this process reduced waste, lowered energy consumption and could be used to produce softer cheeses<sup>12</sup>.

In<sup>32</sup> reported that ultrasound improved the action of *Lactobacilli* in the rate of nearly 50% and also induced a sweetening effect in yogurt without increasing the caloric content. Ultrasonic applications can be applied to all types of products in the food industry.

Ultrasonic techniques also can be used to assess the ripening degree of some fruits. In these applications, the change of physicochemical characteristics, such as textural properties or sugar content, has been related to ultrasonic parameters such as velocity and attenuation. These ultrasonic techniques have been mainly used to assess the concentration, structure, location and physical state of different components in food products<sup>5</sup>.

The use of ultrasonic velocity to estimate the concentration of a given component in a multiphase system has been quite successful. This technique will need to be commercially developed further to be used on a large scale in the food industry<sup>15</sup>.

As we mentioned above, ultrasonication

is commonly used for inactivation of enzymes. Although ultrasound waves deactivate enzymes or destroy microorganisms alone, combinations with other physical treatments are being tried<sup>19</sup>. The action of ultrasound in combination with conventional heat treatment is quite effective in deactivating peroxidase suggesting that this technique has interesting possibilities in food technology. It has been demonstrated that the efficiency of the combined treatment can be related to the ultrasound power density, i.e. the ultrasound power per unit area of tip of the probe and unit volume of liquid treated. In addition, the experimental evidence suggests that there exists a frequency-power density combination which corresponds to the maximum efficiency of the treatment and that the deactivation dynamics is the same whether the treatment is performed in batch or continuous mode<sup>12</sup>.

MTS (Manothermosonication) has been shown to inactivate several enzymes and microorganisms much more rapidly than heat treatment at identical temperatures. The industrial use of MTS could therefore reduce substantially treatment times of several foods. But before MTS can be industrially used, its effects on several quality parameters of these individual foods need to be studied<sup>35</sup>.

In<sup>17</sup> the combined effects of heat and ultrasonic waves operating at absolute pressures between 1.6 and 7.1 kg-2 cm on peroxidase, polyphenol oxidase and lipoxygenase inactivation has been studied. According to this study, a synergistic effect which can substantially reduce enzyme resistance and heat treatment required for inactivation was observed in all cases. The enzyme destruction efficiency of the combined process greatly increases with ultrasonic wave amplitude; decimal reduction times at constant temperature decreased logarithmically with increasing amplitudes. As a conclusion of this study it's reported that this combined treatment could help to solve the problems caused by thermostable enzymes in milk, juices and other drinks.

In<sup>34</sup> free radical formation by manothermosonication under different conditions has been investigated. According to the results of their study, increasing temperature resulted in a decrease in the rate of hydroxyl radical production. Temperature effects were studied between 35 and

145°C at 110 pm ultrasound amplitude. The ultrasound amplitude was varied between 25 and 140 pm at two different temperatures and pressures (75°C/200kPa and 135°C/500kPa). In both cases, free radical production rate increased linearly with increasing ultrasound amplitude. The pressure effects on free radical formation were studied under two different conditions at 115 pm: 75 and 135°C. At 75°C an increase of hydrostatic pressure resulted in an increase in free radical production rate; whereas increasing hydrostatic pressure at 130°C had a negligible effect on free radical production<sup>35</sup>.

A new prototype of a multi-sample ultrasonic dehydration system based on the application of high-amplitude ultrasonic vibrations in direct contact with food samples at low temperatures and together with vacuum, forced-air and static pressure, at pre-industrial stage has been designed, constructed and tested in<sup>11</sup>. First experimental trials were carried out to study the influence of ultrasonic power (0, 25, 50, 75 and 100 W) in the kinetics of the dehydration process. In all trials the temperature and relative humidity were kept between 24-25°C and 30-45%, respectively. The applied static pressure was fixed at 0.065 kg-cm, the suction at 65 mbar and the air flow velocity and temperature at 2 m/s and 35°C, respectively. Moisture content of samples was measured by weighing them at fixed intervals of 15 min. The results clearly show the strong influence of the acoustic intensity in the process. The curves obtained up to a maximum power applied of 100 W reveal a direct increase of the drying effect with the acoustic intensity and no saturation was reached. The use of the present prototype of ultrasonic drying system has so confirmed the role of the main ultrasonic parameter when the other thermo-mechanical parameters (temperature, flow rate, suction, etc.) are kept constants. It is provided with electromechanical and pneumatic elements together with the software and hardware necessary for the automatic control and monitoring of all the variables of the process<sup>11</sup>.

#### **Ultrasonic methods used for microbial inactivation**

Ultrasound technology can be very useful for minimal processing because transfer of acoustic energy to the food product is instantaneous and is distributed throughout the whole product volume. This means a reduction of the total

processing time, higher throughput and lower energy consumption. As<sup>11</sup> has reported, the advantages of ultrasound include: the minimizing of flavor loss, especially in sweet juices; greater homogeneity and significant energy savings.

Ultrasound in its most basic definition refers to pressure waves with frequency of 20 kHz or more<sup>6</sup>. Higher power ultrasound at lower frequencies (25-100 kHz), which is referred to as "power ultrasound" has the ability to cause cavitation, which has uses in food processing to inactivate microbes<sup>11</sup>. The ultrasonic frequency must be under 2.5 MHz, because cavitation does not occur above that level<sup>2</sup>. The effects of cavitation on microbial suspensions are; dispersion of clumps of microorganisms, modification of cellular activity, puncturing of the cell wall and an increased sensitivity to heat. The mechanism of ultrasound for biological cell destruction may be explained by the collapse of cavitation bubbles. Usually a 20 kHz frequency is used. Ultrasonic waves generate cavitation fields which damage the cell wall and maybe also the cytoplasmic membrane. Furthermore they lead to modifications in the cellular structure of yeasts<sup>7</sup>.

The mechanism of microbial inactivation can be attributed to intracellular cavitation. Micro-mechanical shock waves are created by making and breaking microscopic bubbles induced by fluctuating pressures under the ultrasonication process. These shock waves disrupt cellular structural and functional components and lead to cell lysis<sup>33</sup>.

The effect of ultrasound on killing of Gram-negative and Gram-positive bacteria is unclear. It has been reported that Gram-negatives are less resistant to ultrasound waves than Gram-positives<sup>33</sup>. As a result of another study, no significant difference was found in killing rate of two kinds of microorganisms by ultrasonication<sup>1,31</sup>. In<sup>33</sup> Gram-negative and rod-shaped bacteria seem to be more vulnerable to sonication than Gram-positive and coccus-shaped cells has been reported<sup>2,33</sup>. Other factors that affect the inactivation of microbes by ultrasound are known to be the amplitude of the ultrasonic waves, exposure/contact time, volume of food being processed, the composition of the food and the treatment temperature<sup>33</sup>.

The limited current literature indicates that

pathogens are resistant to ultrasound treatment, especially when it is used alone. If ultrasound is combined with other methods a greater antimicrobial potency can be obtained in many cases, combinations of conventional method with ultrasound treatment gave the best result<sup>13</sup>. The combination of heat and ultrasound was reported to be more efficient with respect to treatment time and energy consumption compared to either treatment individually<sup>18,23</sup>. Because of the benefits of these combinatorial treatments, many studies have been performed and the sonication term was derived to manosonication (combination with pressure treatment), thermosonication (combination with heat treatment) and manothermosonication (combination with heat and pressure). In<sup>20</sup> also suggested that inactivation of microbes using ultrasound is effective when used in combination with other decontamination methods such as decreasing pH or chlorination.

Reducing also acts synergistically to enhance the effectiveness of ultrasonic treatment. Such a synergy was demonstrated for the inactivation of *Salmonella enterica* serovar Enteritidis by ultrasound<sup>3</sup>.

According to<sup>27</sup> pressure alone (600 kPa) did not influence the heat resistance of *Yersinia enterocolitica*. At a temperature of 58°C, the lethality of UW under pressure was greater than that of heat treatment alone at the same temperature. At higher temperatures, this difference disappeared. Heat and UW under pressure seemed to act independently. The lethality of MTS treatments appeared to result from the added effects of UW under pressure and the lethal effect of heat. The individual contributions of heat and UW under pressure to the lethal effect of MTS depended on temperature<sup>27</sup>.

In a study evaluating the germicidal efficacy of ultrasonic energy, aqueous suspensions of specific bacteria, fungi and viruses were exposed to an ultrasonic frequency of 25 kHz<sup>31</sup>. This frequency was chosen to maximize the potential for ultrasonically induced cavitation and also to be above the frequency level of human hearing. The selected microorganisms were the bacteria *Escherichia coli*, *Staphylococcus aureus*, *Bacillus subtilis*, *Trichophyton mentagrophytes*, a fungus and feline herpes virus type 1 and feline calivirus. As a result of this study, a significant effect of

intensity was observed for all the bacteria, except *E. coli*. A significant reduction was detected in fungal growth compared to the control group as well as the reduction in populations of feline herpes virus, but there was no apparent effect of ultrasound on feline calicivirus<sup>31</sup>.

There is a paucity of literature on the application of ultrasonics to solid foods such as poultry. In<sup>29</sup> pre- and post-chill broiler drumsticks submerged in deionized water to 47 kHz in an ultrasonic cleaning tank has been exposed. Sonication was applied for 15 or 30 min at 20 or 40°C and for shorter intervals (0.5, 2 and 4 min) in the presence of lactic acid, with pH adjusted to 2 or 4. There was no significant difference in total aerobic bacteria for controls or sonicated thighs when stored for 0, 7 or 14 days at 5°C<sup>29</sup>.

Sonication of *Salmonella* inoculated on broiler skin with and without chlorination was studied by Lillard. Sonication of *S. Typhimurium* cell suspensions (108 cells mL<sup>-1</sup> of peptone) at 25 kHz confirmed the time-dependent reduction shown in<sup>37</sup> the log count decreased to nondetectable levels after sonication for 50 min Lillard showed that salmonellae which were attached to broiler skin were reduced by 1-1.5 log by sonication in peptone at 20 kHz for 30 min; by < 1 log by chlorine alone; but by 2.5-4 log by sonicating skin in a chlorine solution with 0.5 ppm free residual chlorine. Also the use of ultrasonication to destroy *S. Typhimurium* in brain heart infusion broth, skim milk and liquid whole egg has been examined. When *S. Typhimurium* was treated in Bill broth for 30 min, cell numbers decreased by more than 3 log at 40°C and by 1 log at 20°C. In skim milk, a 30-min treatment at 50 and 40°C resulted in 3.0 and 2.5 log reductions, respectively. The microorganisms were more resistant in liquid whole egg; a maximum of <1-log reduction was found with 30 min treatment at 50°C. It was proposed that this was a result of egg constituents protecting the microorganism from the inhibitory effects of cavitation<sup>37</sup>.

*Salmonella Enteritidis*, *S. Typhimurium* and *Salmonella Senftenberg* were investigated for their resistance to heat treatment, manosonication and manothermosonication in liquid whole eggs and citrate phosphate buffer solution. With manosonication (117 pm, 200 kPa, 40°C), *S. Enteritidis*, *S. Typhimurium* and *S. Senftenberg* had

decimal reduction times of 0.76, 0.84 and 1.4 min in whole egg and 0.73, 0.78 and 0.84 min in citrate phosphate buffer, respectively. In comparison, the D-values at 60°C were 0.068, 0.12 and 1.0 min for the buffer and 0.12, 0.20 and 5.5 min for the whole egg, respectively. A linear increase in ultrasonic wave amplitude resulted in an exponential increase in the inactivation rate of the manosonic treatment. When manothermosonication (117 pm, 200 kPa and 60°C) was attempted, an additive effect of the two other treatments (heat and manosonication) resulted. *S. Seftenberg* which is the most resistant of the *Salmonella* serovars to heat treatment could only be reduced by 0.5 log cycle; however, a 3-log cycle reduction was obtained when manothermosonication was applied<sup>18</sup>. In<sup>21</sup> the treatment of milk with ultrasound caused an elimination of 93% of coliforms has been found.

Ince and Belen (2001) observed that the concentration of *E. coli* in deionized water decreased with treatment time at 20 kHz of sonication and that added solids (ceramic granules, metallic zinc particles and activated carbon) improved the inactivation of *E. coli*.

Ultrasonic treatment (20 kHz and amplitude of 117 pm) at ambient temperature was found to be ineffective on *Listeria monocytogenes* giving a decimal reduction time of 4.3 min<sup>25</sup>. By combining sonication with a pressure of 200 kPa, the D-value of the ultrasonic treatment was reduced to 1.5 min. A further increase in pressure to 400 kPa reduced the D-value to 1.0 min. On the other hand, *L. monocytogenes* cultures that were incubated at 37°C were found to be twice as heat resistant as those grown at 4°C; however the cell growth temperature did not change the effect of manosonication treatment<sup>25</sup>.

Comparisons between *Bacillus subtilis* spores treated with manosonication and manothermosonication showed that the heat treatment provided by manothermosonication makes the inactivation process more effective<sup>28</sup>. The simultaneous use of heat and ultrasonic waves could reduce the heat resistance of two strains of *B. subtilis* substantially at atmospheric pressure and temperatures in the range 70-90°C<sup>13</sup>.

Heat resistance of the spores of *Geobacillus stearothermophilus* was reduced when subjected to ultrasonic treatment. It is suggested that the high pressure due to sonication

affected the permeability of the spore protoplast membrane, resulting in the release of dipicolinic acid, calcium and other low molecular weight substances. It may also have allowed the entrance of water from the external environment, which would have reduced the heat resistance<sup>26</sup>. In<sup>4</sup> cellular injury in cells of *E. coli* and *Lactobacillus rhamnosus* in response to a high-intensity ultrasound treatment has been examined. According to their results, the Gram-positive bacterium, *L. rhamnosus*, was more resistant to the lethal effect of ultrasound in comparison with the gram-negative *E. coli*<sup>4</sup>.

#### ACKNOWLEDGEMENT

This research was partially supported by Yasooj Branch of Islamic Azad University. We thank our colleagues from food science and technology department that provided insight and expertise that greatly assisted the research, although they may not agree with all of the interpretations of this paper.

#### REFERENCES

1. Ahmed, F.I.K. and C. Russell, Synergism between ultrasonic waves and hydrogen peroxide in the killing of microorganisms. *J. Applied Bacteriol.*, 1975; **39**: 31-40
2. Alliger H., 2009. Ultrasonic disruption. *Am. Lab.*, **10**: 75-85.
3. Alvarez, I., P. Manas, F.J. Sala and S. Condon, Inactivation of *Salmonella enterica* serovar Enteridis by ultrasonic waves under pressure at different water activities. *Applied Environ. Microbiol.*, 2003; **69**: 668-672.
4. Ananta, E., D. Voigt, M. Zenker, V. Heinz and D. Knorr, Cellular injuries upon exposure of *Escherichia coli* and *Lactobacillus rhamnosus* to high-intensity ultrasound. *J. Applied Microbiol.*, 2015; **99**: 271-278.
5. Benedito, J., J.A. Carcel, R. Gonzalez and A. Mulet, Application of low intensity ultrasonics to cheese manufacturing process. *Ultrasonics*, 2012; **40**: 19-23.
6. Butz, P. and B. Tauscher, Emerging technologies: Chemical aspects. *Food Res. Int.*, 2002; **35**: 279-284.
7. Ciccolini, L., P. Taillandier, A.M. Wilhelm, H. Delmas and P. Strehaiano, Low frequency thermo-ultrasonication of *Saccharomyces cerevisiae* suspensions: Effect of temperature and

- ultrasonic power. *Chem. Eng. J.*, 1997; **65**: 145-149.
8. Crosby, L., Juices pasteurized ultrasonically. Food Production/Management 1982.
  9. De Gennaro, L., S. Cavella, R. Romano and P. Masi, The use of ultrasound in food technology I: in activation of peroxidase by thennosonication. *J. Food Eng.*, 1999; **39**: 401-407.
  10. Earnshaw, R.G., J. Appleyard and R.M Hurst, Understanding physical inactivation process: Combined preservation opportunities using heat, ultrasound and pressure. *Int. J. Food Microbiol.*, 1995; **28**: 197-219.
  11. Fuente-banco, S., D.E. Riera-franco, E. Sarabia and V.M. Acosta-aporicio, Food drying process by power ultrasound. Ultrasonics, article in Press 2006.
  12. Gaffney, B., Sonic converting sounds good to cheese makers. Food Engineering 1996.
  13. Garcia, M., J. Burgos, B. Sanz and A.J. Ordonez, Effect of heat and ultrasonic waves on the survival of two strains of Bacillus's subtilis. *J. Applied Bacteriol.*, 1991; **71**: 445-451.
  14. Ince, N.H and R Helen, Aqueous phase disinfection with power ultrasound: Process kinetics and effect of solid catalysts. *Environ. Sci. Tech.*, 2011; **35**: 1885-1888.
  15. Javanaud, C., Applications of ultrasound to food systems. *Ultrasonics*, 1998; **26**: 117-123.
  16. Kivela, T., Easier cheese mould cleaning by ultrasonics. *Scand. Dairy Infom.*, 1996; **10**: 34-35.
  17. Lopez, P., F.J. Sala, J.L. Fuente, S. Condon, J. Raso and Burgos, Inactivation of peroxidase, lipooxtgenase and polyphenol oxidase by manotherrnosonication. *J. Agric. Food Chem.*, 1994; **42**: 252-256.
  18. Manas, P., R. Pagan, J.P. Raso, F.J. Sala and S. Condon, Inactivation of Salmonella typhimurium and Salmonella senftenberg by ultrasonic waves under pressure. *J. Food Prot*, 2010; **63**: 451-456.
  19. Mason, T .J., J.P. Lorimer and D.M. Bates, Quantifying Sonochemistry: Casting some light on a "Black Art". *Ultrasonics*, 1992; **30**: 40-42.
  20. Mcclements, D.J., Advances in the application of ultrasound in food analysisi and processing. *Trends in Food Sci. Tech.*, 1995; **6**: 293-299.
  21. Munkacsi, F and M. Elhami, Effect of ultrasonic and ultraviolet irradiation on chemical and bacteriological quality of milk. *Egyptian J. Dairy Sci.*, 1976; **4**: 1-6.
  22. Oagan, R., Resistencia frente al calor los ultrasonidos bajo prison de Aeromonas hydrophila, Yersinia enterocolitica, Listeria monocytogenes. Ph D. thesis. University of Zaragoza, Zaragoza, Spain 1977.
  23. Ordonez, JA., M.A. Aguilera, M.L. Garcia and B. Sanz, Effect of combined ultrasonic and heat treatm-ent (thermoultrasonication) on the survival of strain of Staphylococcus aureus. *J. Dairy Res.*, 1987; **54**: 61-67.
  24. Ordonez, IA., B. Sanz, P.E. Hernandez and P. Lopez-lorenzo, A note on the effect of combined ultrasonic and heat treatments on the survival of thermoduric streptococci. *J. Applied Bacteriol.*, 1984; **54**: 175-177.
  25. Pagan, R., P. Manas, J. Raso and S. Condon, Bacterial resistance to ultrasonic waves Ander pressure at nonlethal and lethal (manothermosonication) temperatures. *Applied and Environ. Microbiol.*, 1999; **65**: 297-300.
  26. Palacios, J., J. Burgos, L. Hoz, B. Sanz and J.A. Ordonez, Study of substances released by ultrasonic treatment from Bacillus stearothermophilus spores. *J. Applied Bacteriol.*, 1991; **71**: 445-451.
  27. Raso, J., A. Palo, R. Pagan and S. Condon, Inactivation of bacillus subtilis spores by combining ultrasonic waves under pressure and mild heat treatment. *J. Applied Microbiol.*, 1988; **85**: 849-854.
  28. Raso, J., R. Pagan, S. Condon and F.J. Sala, Influence of temperature and pressure on the lethality of ultrasound. *Applied Environ. Microbiol.*, 1998; **64**: 465-471.
  29. Sams, A.R and R. Feria, Microbial effects of ultrasonication of broiler drumstick skin. *J. Food Sci.*, 1991; **56**: 247-248.
  30. Sanz, P., P. Palacios, P. Lopez, J.A. Ordinez, Effect of Ultrasonic Waves on the Heat Resistance of Bacillus Stearothermophilus Spores. In: Fundamental and Applied Aspects of Bacterial Spores (Eds. ), Dring, G.J., Ellars D.J. and Gould G.W. , New York, pp: 251-259 1985.
  31. Scherba, G., R.M. Weigel and W.D. 'Brien, Quantitive assessment of the germicidal efficacy of ultrasonic energy. *Applied Environ. Microbiol.*, 1991; **57**: 2079-2084.
  32. Toba, T., A new method for manufacture of lactose-hydrolysed fermented milk. *J. Sci. Food Agric.*, 1990; **52**: 403-407.
  33. USDA: Food and Drug Administration Report Kinetics of m icrobial inactivation for alternative food processing technologies: Ultrasound. Published June 2, 2000. available at <http://www.vm.cfsan.fda.gov/>.
  34. Vercet, A., C. Sanchez, J. Burgos, L. Montanes and P.L. Buesa, The effects of manothrrnesonication on tomato pectic enzymes

- and tomato paste rheological properties *J. Eng.*, 2002; **53**: 273-278.
35. Vercet, A., P. Lopez and J. Burgos, Free Radical formation by manothernosonication. *Ultrasonics*, 1998; **36**: 615-618.
36. Willamiel, M and P. De Jong, Inactivation of *Pseudomonas fluorescens* and *Streptococcus thermophilus* in Trypticase® Soy Broth and total bacteria in milk by continuous-flow ultrasonic treatment and conventional heating. *J. Food Eng.* 2010; **45**: 171-179.
37. Wrigley, D.M and N.G. Llorca, Decrease of *Salmonella typhimurium* in skim milk and egg by heat and ultrasonic wave treatment. *J. Food Prot.*, 1992; **55**: 678-680.
38. Wu, H., G.J. Hulbert and J.R. Mount, Effects of ultrasound on milk homogenization and fermentation with yogurt starter. *Innovative Food Sci. Emerging Tech.*, 2011; **1**: 211-218.